
7500 Series








Single Cover • Duct Cover • Multipart Cover



7500 SERIES SPECIFICATIONS

FLOOR FINISHES:	All types of hard floor finishes including ceramic tiles, marble, terrazzo, concrete, resin, wood or parquet.
PERFORMANCE:	Cars and light delivery vehicles up to 5 tonne (5,000kg) pneumatic tyre wheel load.
FEATURES and BENEFITS:	Can be fitted quickly and unobtrusively, ensuring minimum disruption. Unique cover sections are tapered for easy removal, frame sections give a good key to bedding mortar. Double seals available. Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof. Provides easy access to underfloor services using lifting keys or Cover Skate. Aluminium covers are available with a top edge seal to help prevent dirt, grout or grinding waste ingress.
FIRE RATING:	To BS 476: Part 20: 1987 - 3 hours for Single cover, 2 hours for Duct and Multipart covers.
SIZES:	See range overview (overleaf)
WEIGHT:	Approx. 155kg/m² when filled with concrete.
INSTALLATION:	Go to www.howegreen.com



Product Overview

All access covers are made to measure to the minimum and maximum dimensions, in either direction, given below. Some covers are available in stock sizes for more urgent deliveries. Contact office for details.

FLOOR ACCESS COVERS REQUIRING INFILL

	LOADING	COVER TYPE	DEPTH		CLEAR INTERN	CLEAR INTERNAL OPENING		OVERALL FRAME SIZE	
HARD SURFACES	Bespoke loading available for most hatches. Contact office for details.		Overall Frame Depth	Max. Flooring Thickness	Minimum Dimensions	Maximum Dimensions	Minimum Dimensions	Maximum Dimensions	BS476 Part 20: 1987
Solid Hardwood, Timber Strip and Heavy Duty Laminates			A	В		C		D	
2500 Series - Stainless Steel	Light - Pedestrian	Single	25mm	22mm	100mm	Contact office	220mm	Contact office	-
Ceramic Tiles, Marble, Terrazzo, Concrete, Resin, Parquet Floors									
5000 Series - Aluminium	Light - Pedestrian	Single	50mm	18mm	100mm	750mm	220mm	870mm	1 hour
		Duct	50mm	18mm	100mm span	600mm span	220mm	720mm span	-
		Multipart	50mm	18mm	As required	As required, any length	As required	As required, any length	-
5000 Series - Stainless Steel	Light - Pedestrian	Single	50mm	15mm	100mm	750mm	230mm	880mm	1 hour
		Duct	50mm	15mm	100mm span	600mm span	230mm	730mm span	-
		Multipart	50mm	15mm	As required	As required, any length	As required	As required, any length	-
7500 Series - Aluminium	Medium - Cars up to 5 Tonnes	Single	75mm	32mm	100mm	900mm	220mm	1020mm	3 hours
		Duct	75mm	32mm	100mm span	900mm span	220mm	1020mm span	2 hours
		Multipart	75mm	32mm	As required	As required, any length	As required	As required, any length	2 hours
7500 Series - Stainless Steel	Medium - Cars up to 5 Tonnes	Single	75mm	40mm	100mm	900mm	230mm	1030mm	3 hours
		Duct	75mm	40mm	100mm span	900mm span	230mm	1030mm span	2 hours
		Multipart	75mm	40mm	As required	As required, any length	As required	As required, any length	2 hours
TER Series - Aluminium (hinged)	Light - Pedestrian	Single	89mm	25mm	610mm	1065mm	814mm	1269mm	-
		Double	89mm	25mm	1220mm	1830mm	1424mm	2034mm	-
FR Series - Aluminium (hinged)	Light - Pedestrian	Single	89mm	N/A	597mm	1168mm	962mm	1422mm	2 hours
HSE 75 Series - Aluminium (hinged)	Medium - up to 5 Tonnes	Single	75mm	32mm	550mm*	1000mm*	683mm	1133mm	3 hours
		Duct	75mm	32mm	550mm* span	1000mm* span	683mm span	1133mm span	2 hours
		Multipart	75mm	32mm	Contact office	Contact office	Contact office	Contact office	2 hours
HSE 75 Series - Stainless Steel (hinged)	Medium - up to 5 Tonnes	Single	75mm	40mm	550mm*	1000mm*	697mm	1147mm	3 hours
		Duct	75mm	40mm	550mm* span	1000mm* span	697mm span	1147mm span	2 hours
		Multipart	<i>7</i> 5mm	40mm	Contact office	Contact office	Contact office	Contact office	2 hours
All types of hard surfaces including External Grade Paving Slabs (i.e. Granite and Concrete)					* Size does not include	e hardware obstructions			
1050 Series - Stainless Steel	Heavy - up to 6.5 Tonnes	Single	105mm	70mm	100mm	900mm	230mm	1030mm	3 hours
		Duct	105mm	70mm	100mm span	900mm span	230mm	1030mm span	2 hours
		Multipart	105mm	70mm	As required	As required, any length	As required	As required, any length	2 hours
Tree Pit Covers									
5000 Series - Aluminium	Light - Pedestrian	Tree Pit	50mm	20mm	100mm	750mm	230mm	870mm	-
- Stainess Steel			50mm	22mm	100mm	750mm	230mm	880mm	-
7500 Series - Aluminium	Medium - Cars up to 5 Tonnes	Tree Pit	75mm	32mm	100mm	900mm	230mm	1020mm	-
- Stainess Steel			<i>7</i> 5mm	40mm	100mm	900mm	230mm	1030mm	-
1050 Series - Stainless Steel	Heavy - up to 6.5 Tonnes	Tree Pit	105mm	70mm	100mm	900mm	230mm	1030mm	-
FLEXIBLE SURFACES	For all types of flexible floo	ring, Vinyl, Linole	eum, Rubber, som	e Carpets					
Visadas® Savina Alumini	links David vi	C:I	50	2.4	150	1000 1000	227	1107 1007	
Visedge® Series - Aluminium	Light - Pedestrian	Single Duct	50mm 50mm	2-4mm 2-4mm	150mm 150mm span	1000-1200mm 1000mm span	237mm 237mm span any length	1137-1337mm 1137mm span any length	-

6 www.howegreen.com Tel: +44 (0) 1920 463 230 www.howegreen.com Tel: +44 (0) 1920 463 230

As required

As required

As required

As required

2-4mm

Multipart

50mm

Product Overview

SOLID FLOOR ACCESS COVERS NO INFILL REQUIRED

									* ***
	LOADING Bespoke loading available for most hatches. Contact office for details.	COVER TYPE	DEPTH		CLEAR INTERNAL OPENING		OVERALL FRAME SIZE		FIRE RATED
HARD SURFACES			Overall Frame Depth	Max. Flooring Thickness	Minimum Dimensions	Maximum Dimensions	Minimum Dimensions	Maximum Dimensions	BS476 Part 20: 1987
JFR Fire Doors - Stainless Steel	Light - Pedestrian	Single	89mm	-	610mm	1830mm	826mm	2046mm	1 hour
5 Bar Series Tread Plate - Aluminium	Light - Pedestrian	Single	50mm	-	150mm	1000mm	287mm	1137mm	-
		Duct	50mm	-	150mm clear span	1000mm span, any length	287mm span	1137mm span, any length	-
J-AL Drainage Doors - Aluminium	Light - Pedestrian	Single	89mm	-	610mm	1220mm	762mm	1370mm	-
		Double	89mm	-	760mm	1830mm	912mm	1982mm	-
J-AL H20 Drainage Doors - Aluminium	Heavy - up to 14.5 Tonnes	Single	89mm	-	610mm	1065mm	762mm	1319mm	-
		Double	89mm	-	760mm	1830mm	1014mm	2084mm	-

SPECIAL APPLICATIONS

We can provide solutions to many unique and special applications. Please contact office to discuss any unusual requirements you may have.

CHANNEL DRAIN SOLUTIONS

Most types of finish in changing rooms, shower areas, spas, kitchens, laboratories, veterinary surgeries etc.

HG100 - Stainless Steel (Light - Pedestrian).
HG200 - Stainless Steel (Consult office for details).

EDGE TRIMMINGS

HARD AND FLEXIBLE SURFACES

VISEDGE® DS SERIES

Aluminium trim to secure and protect the edge of vinyl/linoleum flooring when laid on top of another surface, such as ceramic tiles. It is used to securely anchor the perimeter of the flexible flooring.

VISEDGE® VR SERIES

A vinyl edge securing trim with a weldable PVC edge, enabling two differing floor finishes (eg vinyl and terrazzo) to be finished flush. It prevents the ingress of water and protects the edge profile of the adjoining flooring.

Visedge® DS and VR Series Edge Trims - Packs of 5 (2m lengths).

FIXED VERTICAL LADDERS

All Ladders: 488mm wide in standard lengths between 2m and 6m. Special sizes available on request.

TYPE BL	- Aluminium - Mild Steel	No safety cage.
TYPE BL-WH	- Aluminium - Mild Steel	Safety cage.
TYPE BL-WG	- Aluminium - Mild Steel	Safety cage and guardrail.


SAFETY AND MAINTENANCE PRODUCTS

LadderUp™ Safety Post
Cover Skate
Lifting Key
Replacement Bolt

HELP AND ADVICE

Access Cover Sizes

Our diagram below answers the most common questions.



- OVERALL FRAME DEPTH of access cover including frame
- MAXIMUM FLOORING THICKNESS for inset to cover
- CLEAR INTERNAL OPENING = size of access gap through frame
- OVERALL FRAME SIZE = footprint of access cover including frame

Duct and Mulitpart Design

Please contact office for details of beams and pockets.

8 www.howegreen.com Tel: +44 (0) 1920 463 230 9