## Visedge<sup>®</sup> Series





#### Single Cover • Duct Cover • Multipart Cover



#### **VISEDGE® SERIES SPECIFICATIONS**

FLOOR FINISHES: All types of flexible sheet flooring, e.g. PVC, vinyl, rubber, linoleum and some carpets. **PERFORMANCE:** Pedestrian traffic (including wheeled trolleys, sack trucks etc.) only. **FEATURES** Can be fitted quickly and unobtrusively, ensuring minimum disruption. and BENEFITS: The PVC extrusion is locked to the frame sections, bonded and welded to the cut edge of the sheet flooring. This creates a flat, The aluminium and steel construction is tough, light and corrosion resistant. Crimped corners allow the cover and frame to lie completely flat. The unique Howe Green double seal construction forms the most positive seal to drainage, electrical and other ducts. Provides easy access to underfloor services using lifting keys. Trade mark registration numbers 000807842 (EU) and 00001471054 (UK). SIZES: See pages 6-7. **WEIGHT:** Approx. 30kg/m<sup>2</sup>. **INSTALLATION:** Go to www.howegreen.com



# Visedge® DS Series







### **Securing Edge Trim**

Secures and protects the edge of flexible flooring when it has been laid on top of another surface.



#### VISEDGE® DS SPECIFICATIONS

USAGE:	Anchors securely the perimeter of the vinyl flooring.
FLOOR FINISHES:	For junctions of flexible sheeting (e.g. vinyl or linoleum) and hard paving (e.g. ceramic tiling etc.).
PERFORMANCE:	Pedestrian traffic (including wheeled trolleys, sack trucks etc.) only.
MAINTENANCE FREE:	Designed to ensure accurate and unobtrusive installation with no further maintenance once installed.
SIZES:	Supplied in packs of 5 x 2m lengths.
INSTALLATION:	Go to www.howegreen.com

# Visedge® VR Series









### **Securing Edge Trim**

Enables the smooth flush-joint transition between two different floor finishes, such as vinyl and terrazzo.



#### VISEDGE® VR SPECIFICATIONS

INSTALLATION:	Go to www.howegreen.com
SIZES:	Supplied in packs of 5 x 2m lengths.
MAINTENANCE FREE:	Designed to ensure accurate and unobtrusive installation with no further maintenance once installed.
PERFORMANCE:	Pedestrian traffic (including wheeled trolleys, sack trucks etc.) only.
FLOOR FINISHES:	For junctions of flexible sheeting (e.g. vinyl or linoleum) and hard paving (e.g. ceramic tiling etc.).
USAGE:	Anchors securely the perimeter of the vinyl sheeting to prevent the ingress of water and protects the edge profile of the adjoining ceramic tile paving, forming an impermeable, flat, hygienic and permanent joint.

Tel: +44 (0) 1920 463 230 Tel: +44 (0) 1920 463 230 www.howegreen.com www.howegreen.com